


SOT-89-3L Plastic-Encapsulate Transistors

BCX55 TRANSISTOR (NPN)

• Features

- Complimentary to BCX52



1. BASE
2. COLLECTOR
3. EMITTER

SOT-89-3L

• MAXIMUM RATINGS (T_C=25°C)

Parameter	Symbol	Limit	Unit
Collector-Base Voltage	V _{CBO}	60	V
Collector-Emitter Voltage	V _{CEO}	60	V
Emitter-Base Voltage	V _{EBO}	5	V
Collector Current	I _C	1	A
Collector Power Dissipation	P _C	500	mW
Thermal Resistance From Junction To Ambient	R _{θJA}	250	°C/W
Operation Junction and Storage Temperature Range	T _J , T _{stg}	-55~+150	°C

• ELECTRICAL CHARACTERISTICS (T_a=25°C)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	V _{(BR)CBO}	I _C =100μA, I _E =0	60			V
Collector-emitter breakdown voltage	V _{(BR)CEO} *	I _C =10mA, I _B =0	60			V
Emitter-base breakdown voltage	V _{(BR)EBO}	I _E =10μA, I _C =0	5			V
Collector cut-off current	I _{CBO}	V _{CB} =30V, I _E =0			0.1	μA
Emitter cut-off current	I _{EBO}	V _{EB} =5V, I _C =0			0.1	μA
DC current gain	h _{FE(1)} *	V _{CE} =2V, I _C =5mA	40			
	h _{FE(2)} *	V _{CE} =2V, I _C =150mA	63		250	
	h _{FE(3)} *	V _{CE} =2V, I _C =0.5A	25			
Collector-emitter saturation voltage	V _{CE(sat)} *	I _C =0.5A, I _B =50mA			0.5	V
Base -emitter voltage	V _{BE} *	V _{CE} =2V, I _C =0.5A			1	V
Transition frequency	f _T	V _{CE} =5V, I _C =10mA, f=100MHz		130		MHz







• CLASSIFICATION OF h_{FE(1)}



Rank	BCX55	BCX55-10	BCX55-16
Range	63 - 250	63 - 160	100 - 250

Ordering Information:


Part NO.	BCX55
Marking	BE/BG/BM
Packing Information	REEL TAPE
Basic ordering unit (pcs)	1000

Typical Characteristics






SOT-89-3L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF.		0.061 REF.	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP.		0.060 TYP.	
e1	3.000 TYP.		0.118 TYP.	
L	0.900	1.200	0.035	0.047



Note:
 1. Controlling dimension: in millimeters.
 2. General tolerance: ± 0.05 mm.
 3. The pad layout is for reference purposes only.