

• Product Summary

Part #	V_{DS}	$R_{DS(on).typ}$ (@ $V_{GS}=10V$)	$R_{DS(on).typ}$ (@ $V_{GS}=4.5V$)	I_D
EFM3442A	100V	514m Ω	530m Ω	1A

• Features


- Low $R_{DS(on)}$ @ $V_{GS}=10V$
- 4.5V Logic Level Control
- N Channel SOT23-3L Package
- Pb-Free, RoHS Compliant

• Application


- Power switching application
- Hard switched and high frequency circuits
- Uninterruptible power supply
- Motor control

• Ordering Information:

Part NO.	EFM3442A
Marking	BC****
Packing Information	REEL TAPE
Basic ordering unit (pcs)	3000



N-Channel MOSFET



SOT23-3L



• Absolute Maximum Ratings ($T_C=25^{\circ}C$)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	1	A
Drain Current-Pulsed ^(Note 1)	I_{DM}	4	A
Maximum Power Dissipation	P_D	1.4	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 150	$^{\circ}C$

• Thermal Characteristic

Thermal Resistance, Junction-to-Ambient ^(Note 2)	$R_{\theta JA}$	100	$^{\circ}C/W$
---	-----------------	-----	---------------

• Static Electrical Characteristics @ T_J = 25°C (unless otherwise stated)



Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V I _D =250uA	100	--	--	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =100VV _{GS} =0V	--	--	1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±20V V _{DS} =0V	--	--	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} I _D =250uA	1.0	1.6	2.5	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =10V I _D =1A	--	514	528	mΩ
		V _{GS} =4.5V I _D =1A	--	530	550	mΩ
Dynamic Characteristics (Note4)						
Input Capacitance	C _{Iss}	V _{DS} =50V V _{GS} =0V F=1.0MHz	--	100	--	PF
Output Capacitance	C _{Oss}		--	13	--	PF
Reverse Transfer Capacitance	C _{rss}		--	5	--	PF
Forward Transconductance	g _{FS}	V _{DS} =5V,I _D =1A	--	2.8	--	S
Switching Characteristics (Note 4)						
Turn-on Delay Time	t _{d(on)}	V _{DD} =50V I _D =1A V _{GS} =10V R _G =3Ω,	--	5	--	nS
Turn-on Rise Time	t _r		--	4	--	nS
Turn-Off Delay Time	t _{d(off)}		--	12	--	nS
Turn-Off Fall Time	t _f		--	5	--	nS
Total Gate Charge	Q _g	V _{DS} =50V I _D =1A V _{GS} =10V	--	2.8	--	nC
Gate-Source Charge	Q _{gs}		--	0.4	--	nC
Gate-Drain Charge	Q _{gd}		--	0.8	--	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V _{SD}	V _{GS} =0V I _S =1A	--	0.79	1.2	V
Diode Forward Current (Note 2)	I _S		--	--	1	A

Notes:



1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production

• Test Circuit



Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



• Typical Characteristics




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)










Figure 6: Body-Diode Characteristics (Note E)



SOT23-3L Package Outline Dimensions



DIMENSIONS (unit : mm)

Symbol	Min	Typ	Max	Symbol	Min	Typ	Max
A	1.00	1.17	1.30	A ₁	0.01	0.05	0.10
b _p	0.35	0.39	0.50	c	0.10	0.20	0.26
D	2.70	2.90	3.10	E	1.30	1.58	1.70
e	--	1.90	--	e ₁	--	0.95	--
H _E	2.50	2.78	3.00	L _p	0.20	0.32	0.60
Q	0.23	0.27	0.33	v	--	0.20	--
w	--	0.20	--				